TORFLEX®

RUBBER TORSION SUSPENSION AXLES

TORSION
600 - 12,000 LBS.
CAPACITY

Print Form Clear Form

Date: 9/21 _____ Account #: _____

Account Name: Nate _____ Contact Person: Nate _____

Phone: (614) 620 7873 _____ Serial/Config #: _____

Axle Model: ☐ #8 ☐ #9 ☐ #10 ☐ #10F ☐ #11 ☐ #12 ☐ #12T ☐ #12V ☐ #13 ☐ #13T ☐ #13N ☐ #13G ☐ #13D ☐ #14
☐ #14T ☐ M9 ☐ M10 ☐ M11 ☐ M12 ☐ M13 ☐ M13N ☐ M1399 ☐ M14 ☐ #12AG ☐ #13AG ☐ #13HAG ☐ #14HAG

Quantity: 1 _____ **Hub Face:** 79 _____ **Outside of Brackets:** 60 _____
Dimensions must be in 1/4" increments Dimensions must be in 1/4" increments

Start Angle: ☐ 45 Degrees Down ☐ 32 Degrees Down (available on select models) ☑ 22.5 Degrees Down ☐ 10 Degrees Down
☐ 0 Degrees ☐ 10 Degrees Up ☐ 22.5 Degrees Up

Axle/Rubber Capacity: _____

Axle Type: ☐ Beam only ☐ Idler Axle ☑ Brake Axle

Brake Flange (Beam & Idler Only): ☐ Yes ☐ No

Spindle Type: ☑ Standard (Long) ☐ Short (Most Common) ☐ Removable Spindles

Lubrication: ☑ Grease ☐ Oil ☐ E-Z Lube® ☐ Nev-R-Lube®

Cambered: ☐ Full ☐ Half ☑ No

Wheel Bolt Pattern: ☐ 4 on 4" ☐ 5 on 4.5" ☐ 5 on 4.75" ☐ 5 on 5" ☐ 5 on 5.5"
☐ 6 on 5.5" ☐ 6 on 6" ☑ 8 on 6.5" ☐ 8 on 8" (AG only) ☐ UTG

Hub/Hub-Drum Finish: ☐ Painted ☐ Zinc Hub ☐ Gal-Dex Hub-Drum

Zinc Plated Studs (Not available on all models): ☐ Yes ☐ No

Idler (#8 & #9 5 on 4.5"): ☐ 5.5" Diameter Hub ☐ 6.5" Diameter Hub

Stud Size: ☑ 1/2" ☐ 9/16" ☐ 5/8" Flgd ☐ 5/8" Coned ☐ Add Clamp Ring w/5/8" Coned ☐ 5/8" w/Swivel Flanged Nuts

Brake Type:
☑ Electric ☐ Uni-Servo Hydraulic ☐ Hydraulic Free Backing Marine
☐ Nev-R-Adjust® Electric ☐ Duo-Servo Hydraulic
☐ Disc Hydraulic ☐ Hydraulic Free Backing

Park (only available on select models): ☐

ABS Package for Hydraulic Brakes (Only available on select models): ☐

Electric Options (not all options are available with all models):
☐ Conduit Wire Protectors ☐ 33" Lead Wires ☐ 32" Braided Wire Sleeves ☐ 24" Pig Tails ☐ 12' Leads

Pre-wired (Not available on all models): ☑ Yes ☐ No

Disc Options (not all options are available with all models):
☐ Zinc H&R, Zinc Caliper ☐ Zinc H&R, Aluminum Caliper ☐ Kodiak Silver, Dak Caliper (#13N Only) ☐ Kodiak Stainless Steel Caliper (#13N Only)

Seal Sleeve (not available on all models): ☐ Yes ☐ No

Mounting Brackets: ☐ Low Profile Brackets ☐ High Profile Brackets ☐ 3" High Profile Brackets
☐ Featherlite Brackets ☐ RT Brackets ☐ Extreme Brackets

Mounting Bracket Orientation: ☑ Standard ☐ Reverse

Shock Mounts: ☐ None ☐ Top ☐ Bottom

Mounting Kits: ☐ Top Mount Kit ☐ Side Mount Kit ☐ Aluminum Side Mount Kit ☐ None

Add Air Flex (available on select models): ☐ Yes ☐ No

Beam Finish: ☐ Painted ☐ Powder Coat ☐ Galvanized ☐ Raw ☐ E-Coat

Notes: _____

IN CASE OF CUSTOMER ERROR:
Dexter builds axles to order per selected customer specifications. Some combinations may not work for your application depending on options selected or not selected in this form. Please be sure **ALL** dimensions and specifications are correct. Customer is responsible for all freight charges incurred with the original shipment. Special ordered axles matching the customer's selection criteria are not eligible for return.

Customer Signature: _____

Axle Request Contact Info: DDG-AxleRequests@dextergroup.com
Phone: 903-855-3444 | Text: 903-289-5516

PREMIUM WARRANTY 5/10 YEARS SPRING AXLES TORFLEX AXLES